SAFETY DATA SHEET

SECTION 1 Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
 - Product Name: No Nonsense Water Repellent Sealer
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - Use of the substance/mixture: A water repellent for exterior brickwork, stone, concrete, masonry etc.
- 1.3 Details of the supplier of the safety data sheet
 - Name of Supplier: No Nonsense Limited
 - Address of Supplier: Trade House

Houndstone Business Park

Yeovil

Somerset BA22 8RT

- 1.4 Emergency telephone number
 - Emergency Telephone: 01226 771600 (Office Hours Only)

SECTION 2 Hazards identification

- 2.1 Classification of the substance or mixture
 - CHIP: Xn:R65. N:R51/53. ,R66,R67, R10
 - CLP:
 - Physical and Chemical Hazards

Flam. Liq. 3

- Human Health

Eye Irrit. 2

Muta. 2

Muta. 1B

Carc. 1B

STOT SE 3

Asp. Tox. 1

- Environment

Aquatic Chronic 2

2.2 Label elements









- Signal Word: Danger
- Hazard phrases
 - H226 Flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H336 May cause drowsiness or dizziness.
 - H319 Causes serious eye irritation.
 - H340 May cause genetic defects by skin contact
 - H350 May cause cancer by skin contact
 - H411 Toxic to aquatic life with long lasting effects.

SECTION 2 Hazards identification (....)

- Precautionary Phrases

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P243 - Take precautionary measures against static discharge.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

2.3 Other hazards

SECTION 3 Composition/information on ingredients

3.1 Substances

3.2 Mixtures

- Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha

CAS Number: 64742-82-1 EC Number: 265-185-4 Concentration: 96.25 %

R/H Phrases: H226,H304,H336,H411 R10,R65,R66,R67,R51/53

Common Name: White Spirit
- 2-methylpropan-1-ol; iso-butanol

CAS Number: 78-83-1 EC Number: 201-148-0 Concentration: 1.045 %

R/H Phrases: H226,H335,H315,H318,H336, R10,R37/38,R41,R67

Common Name:

SECTION 4 First aid measures

- 4.1 Description of first aid measures
 - Contact with eyes

If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes

- Contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of soap and water.

- Ingestion

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

- Inhalation

Remove patient to fresh air

Persons who have inhaled substance may not exhibit symptoms immediately

- 4.2 Most important symptoms and effects, both acute and delayed
 - Eves

Mildly irritating to eyes

- Skin

Prolonged skin contact will result in defatting of the skin, leading to irritation and in some

SECTION 4 First aid measures (....)

cases, dermatitis.

- Ingestion
 - The ingestion of significant quantities may cause damage to lungs
- Inhalation
 - In cases of severe exposure, dizziness, confusion, headache or stupor may develop
- 4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5 Fire-fighting measures

- 5.1 Extinguishing media
 - Extinguish with foam, carbon dioxide or dry agent. Never use water jet.
- 5.2 Special hazards arising from the substance or mixture
 - Decomposition products may include carbon oxides
- 5.3 Advice for firefighters
 - Avoid breathing fumes.
 - Wear protective clothing as per section 8

SECTION 6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 - Shut off all ignition sources
 - Ventilate area
 - Wear protective clothing as per section 8
- 6.2 Environmental Precautions
 - Do not allow to enter public sewers and watercourses
 - If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities
- 6.3 Methods and material for containment and cleaning up
 - Absorb spillage in inert material and shovel up
 - Remove contaminated material to safe location for subsequent disposal
- 6.4 Reference to other sections

SECTION 7 Handling and storage

- 7.1 Precautions for safe handling
 - Ensure adequate ventilation
 - Avoid contact with skin and eyes
 - Do not breathe vapour.
- 7.2 Conditions for safe storage, including any incompatibilities
 - Keep in a cool, dry, well ventilated place
 - Keep away from oxidisers, heat, flames or ignition sources
- 7.3 Specific end use(s)
 - See Section 1.2

SECTION 8 Exposure controls/personal protection

- 8.1 Control parameters
 - WEL (long term) 350 mg/m3
 White Spirit (TWA)

SECTION 8 Exposure controls/personal protection (....)

8.2 Exposure controls

- Wear suitable protective clothing, including eye/face protection and gloves (neoprene are recommended)











SECTION 9 Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
 - Appearance: Clear mobile liquid, with solvent odour
 - Solubility in water: Insoluble in water
 - Specific Gravity: 0.77 0.78Flash point 40 deg C (CC)
 - Boiling Point/Range: 150 degC approx
 - Autoflammability: >200 deg C

9.2 Other information

SECTION 10 Stability and reactivity

10.1 Reactivity

- No hazardous reactions known if used for its intended purpose
- 10.2 Chemical stability
 - Considered stable under normal conditions
- 10.3 Possibility of hazardous reactions
 - No hazardous reactions known if used for its intended purpose
- 10.4 Conditions to avoid
 - Keep away from heat and sources of ignition
- 10.5 Incompatible materials
 - Incompatible with oxidizing substances
- 10.6 Hazardous Decomposition Products
 - Decomposition products may include carbon oxides

SECTION 11 Toxicological information

LD50 (oral,rat) >15000 mg/kg

LD50 (dermal) : Rabbit 3400 mg/kg

LC50 (inhalation,rat) 13.1 mg/l/4h

- 11.1 Information on toxicological effects
 - Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

SECTION 12 Ecological information

12.1 Toxicity

- LC50 (rainbow trout) 10 30 mg/l (96 hr)
- EC50 (Daphnia magna) 10 22 mg/l (96 hr)
- 12.2 Persistence and degradability

SECTION 12 Ecological information (....)

- Readily biodegradable
- 12.3 Bioaccumulation Potential
 - No information available
- 12.4 Mobility in soil
 - No information available
- 12.5 Results of PBT and vPvB assessment
 - Not identified as PBT or vPvB under current EU criteria
- 12.6 Other Adverse Effects

SECTION 13 Disposal considerations

- 13.1 Waste treatment methods
 - Disposal should be in accordance with local, state or national legislation

SECTION 14 Transport information





- 14.1 UN Number
 - UN No.: 1993
- 14.2 UN Proper Shipping Name
 - Proper Shipping Name: Flammable Liquid NOS (contains whirte spirit)
- 14.3 Transport hazard class(es)
 - Hazard Class: 3
- 14.4 Packing group
 - Packing group III
- 14.5 Environmental hazards
 - Marine pollutant
- 14.6 Special precautions for user
 - Tunnel Code: D/E
 - Limited quantity category LQ7
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

SECTION 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - The Chemicals (Hazard Information and Packaging) Regulations applies in the UK
 - The COSHH Regulations apply in the UK
 - The Health and Safety at Work Act applies in the UK
- 15.2 Chemical Safety Assessment
 - A chemical safety assessment (CSA) for this product has not yet been completed

SECTION 16 Other information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- H226: Flammable liquid and vapour. H304: May be fatal if swallowed and enters airways. H315: Causes

SECTION 16 Other information (....)

skin irritation. H318: Causes serious eye damage. H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness. H411: Toxic to aquatic life with long lasting effects. R10: Flammable. R37/38: Irritating to respiratory system and skin. R41: Risk of serious damage to eyes. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.

16.1 Other information

- This SDS has been prepared in accordance with EU regulation 453/2010/EC This information is given in good faith, being based on the latest knowledge available to Siroflex Limited. No known relevant information has been omitted from this Safety Data Sheet and the information provided is designated to enable the user to use the product safely. The user should not assume, on the basis of the information provided in this sheet, that the product is suitable for any abnormal use. If the information provided is insufficient to ensure safety in any particular application, contact Siroflex Limited for further advice before the proposed application is undertaken.