

MATERIAL SAFETY DATA SHEET



Y K TOH MARKETING (S) PTE LTD

MSDS No.	MB0101
Date prepared	080811
page	1 of 3

Section1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: OREX SPRAY PAINT

Chemical Family: Aerosol Paint

Company Identification : 8 Changi North Street 1, Tsk Building, Singapore 498829

Section2: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	CAS No	Contents (weight%)
Acrylic Resin	NA	10-30
Propane	74-98-6	10-20
Butane	106-97-8	10-20
Xylene	1330-20-7	10-30
Acetone	67-64-1	10-30
Butyle Acetate	123-86-4	10-30
Whiting Titanium and other color powder	NA	5-20

Section3: HAZARDS IDENTIFICATION

Skin Contact: Slight skin irritant

Eye Contact: Will cause irritation upon contact

Section4: First Aid Measures

Skin Contact: Wash area with soap and water. seek medical attention if irritation persists

Eye Contact: Immediately flush eyes with plenty of water for 15 minutes. Seek medical attention.

Section5: Fire Fighting Measures

Extinguishing media: CO2, powder, water spray/mist

Page: 2 of 3

Section6: Accidental Release Measures

SPILL/LEAK PROCEDURES: Notify safety personnel ,evacuate all unnecessary personnel and provide adequate ventilation.

SMALL SPILLS: Clean with inert absorbent and place in recovery drums for disposal.

Section7: Handling And Storage

Handling Precautions: Wash thoroughly after handling.Do not use near open flame.

Storage Requirements: Store in clean, dry locations away from excessive heat. Keep out of reach of children.

Section8: Exposure Controls/Personal Protection

Engineering Controls: Eye wash station and safety shower.

General ventilation. Material non - volatile

Protective Equipment:

EYE: Chemical splash goggles with indirect or no ventilation.

SKIN :Chemical resistant gloves, such as nitrile.

Section 9: Physical And Chemical Properties

Appearance	coloured paint
Flash Point	60°C
Specific Gravity @ 20	N/a
Solubility	Insoluble in water; soluble in ketones/esters
Kinematic Viscosity @ 40%(mm ² S-1)	n/a

Section 10: Stability And Reactivity

Stability: Material is stable.

Conditions to avoid: open flame.

Materials to avoid (incompatability): strong acids, strong alkalis

Hazardous Polymerization: Cannot occur.

Section 11: Toxicological Information

There is no data Available on the product itself.

Section 12: Ecological Information

There is no data available on the product itself.

Page: 3 of 3

Section 13: Disposal Consideration

The product should not be allowed to enter drains or water courses or be deposited.

Section 14: Transport Information

DOMESTIC: CONSUMER COMMODITY
UN Number: UN1950
Dangerous Good Class: Class 2.1

Section 15: Regulatory Information

Risk Phrases R: Not applicable.
Safety Phrases S: N/A

Section 16: Other Information

N/A

*****End of MSDS Document.*****